

U.S. DEPARTMENT OF LABOR

Form Approved

Occupational Safety and Health Administration

OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Finnforest Oy	EMERGENCY TELEPHONE NO. 358-12-24331
ADDRESS (Number, Street, City, State, and Zip Code) P.O. Box 24, SF-08101 Lohja, Finland	
CHEMICAL NAME AND SYNONYMS Laminated Veneer Lumber	TRADE NAME AND SYNONYMS Master Plank
CHEMICAL FAMILY Wood	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES & SOLVENTS	%	TLV (Units)	ALLOYS & METALLIC COATINGS	%	TLV (Units)
PIGMENTS:			BASE METAL:		
CATALYST:			ALLOYS:		
VEHICLE:			METALLIC COATINGS:		
SOLVENTS:			FILLER METAL PLUS COATING OR CORE FLUX:		
ADDITIVES:			OTHERS:		
OTHERS:					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Phenol-formaldehyde resin	7	

SECTION III - PHYSICAL DATA

BOILING POINT (°F)		SPECIFIC GRAVITY (H ₂ O=1)	0.5
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (____ = 1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR:			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (method used)	None	FLAMMABLE LIMITS	N/A	LeI:	Uel:
EXTINGUISHING MEDIA:	Water, foam, dry chemicals				
SPECIAL FIRE FIGHTING PROCEDURES:	None				
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None				

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:
EFFECTS OF OVEREXPOSURE:
EMERGENCY AND FIRST AID PROCEDURES:

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE	<input type="checkbox"/>	CONDITIONS TO AVOID:
	STABLE	<input checked="" type="checkbox"/>	
INCOMPATIBILITY (materials to avoid):			
HAZARDOUS DECOMPOSITION PRODUCTS:			
HAZARDOUS	MAY OCCUR:	<input type="checkbox"/>	CONDITIONS TO AVOID:
POLYMERIZATION	WILL NOT OCCUR:	<input checked="" type="checkbox"/>	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
WASTE DISPOSAL METHOD: Recycling or combustion Combustion temperature should exceed 1300F.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type):		
VENTILATION	LOCAL EXHAUST:	SPECIAL:
	MECHANICAL (general):	OTHER:
PROTECTIVE GLOVES: YES / NO		EYE PROTECTION: YES / NO
OTHER PROTECTIVE EQUIPMENT:		

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
OTHER PRECAUTIONS: